LABELITE 25 YW



MACHINABLE POLYURETHANE FOAM BOARD

Density 250 kg.m⁻³

DESCRIPTION

Homogenous polyurethane foam board used in various modeling applications: proof cut of CNC milling software program, mock-ups, design or styling works, core support for large dimensions models (clay, epoxy/PU pastes or wet lay-up FRP).

PROPERTIES

- Good edge resistance
- Excellent dimensional stability

- Superb smooth surface aspect after milling
- Not friable nor powdery

| PHYSICAL PROPERTIES | | | | | | |
|--|---------|-------------------|--|--|--|--|
| Composition | | Polyurethane foam | | | | |
| Colour | | Peach yellow | | | | |
| Specific gravity at 25 ℃ (kg.m ⁻³) | ISO 845 | 250 | | | | |

| MECHANICAL PROPERTIES at 23 °C | | | | | |
|--------------------------------|----------------|---------|-----|--|--|
| Hardness | ISO 868 : 2003 | Shore D | 25 | | |
| Flexural strength | ISO 178 : 2010 | MPa | 5.4 | | |
| Compressive strength at yield | ISO 604 : 2002 | MPa | 3.8 | | |

| THERMAL AND SPECIFIC PROPERTIES | | | | | |
|--|--------------------|----------------------------------|----|--|--|
| Glass transition temperature (tg) | ISO 11359-2 : 1999 | °C | 75 | | |
| Coefficient of thermal expansion (CTE) (+10 °C to +60 °C) | ISO 11359-2 : 1999 | 10 ⁻⁶ K ⁻¹ | 60 | | |

ASSEMBLY / FINISH

LABELITE 25 YW boards can be bonded with Labelite Glue.

HANDLING PRECAUTIONS

Normal health and safety precautions should be observed when handling these products:

- Ensure good ventilation
- Wear gloves, safety glasses and waterproof clothes

For further information, please consult the product safety data sheet.

Page 1/2 - TDS12F0152 - February 19th, 2014

axson@axson.it axson.it





MACHINABLE POLYURETHANE FOAM BOARD

Density 250 kg.m⁻³

STORAGE CONDITIONS

The slabs must b stored in a dry place protected from extremes of temperature.

PACKAGING

 1500x500x50mm
 2000x1000x100mm

 1500x500x100mm
 2000x1000x150mm

 1500x500x200mm
 2000x1000x200mm

GUARANTEE

The information contained in this technical data sheet result from research and tests conducted in our Laboratories under precise conditions. It is the responsibility of the user to determine the suitability of AXSON products, under their own conditions before commencing with the proposed application. AXSON guarantee the conformity of their products with their specifications but cannot guarantee the compatibility of a product with any particular application. AXSON disclaim all responsibility for damage from any incident which results from the use of these products. The responsibility of AXSON is strictly limited to reimbursement or replacement of products which do not comply with the published specifications.

Page 2/2 - TDS12F0152 - February 19th, 2014

ITALY +39 02 96 70 23 36

axson@axson.it axson.it info.middleeast@axson.com axson.com